

121

General Description

- A blend of light hydrotreated distillate.
- This product does not require stirring before use.

Applications

- For professional or consumer use
- For removal of adhesive residue from fabricated parts
- Leaves no film after drying

Applications to Avoid

- Do not use this product to clean equipment (spray guns, fluid lines, hoses, spray pots, rollers, brushes, etc.).
- Do not use this product or any other to thin Wilsonart Adhesives.

Availability

- 55-gallon drums
- 5-gallon pails
- 1-gallon cans

Storage/Shelf Life

- Close container tightly when not in use.
- Rotate stock.
- Shelf life expires 2 years from manufacture date.
- Store in a cool, well-ventilated area and away from ignition sources.

General Use Instructions

- Use only after you have read and understand the warnings, safety measures and first aid instructions printed on container.
- Apply and allow to dry only in a well-ventilated area.
- Use outdoors when possible. If indoors, open all windows and doors, and shut off all sources of ignition.

For Adhesive Residue Removal

- Dab rag in cleaner and lightly rub on residue, increasing rubbing pressure as needed. Keep rag wet with cleaner for best results.

Clean-up/Disposal

- Dispose of waste cleaner and cleaner soaked rags in accordance with regulations.
- Empty container may contain hazardous residue or flammable vapors which may explode upon ignition.
- Do not allow in any sewers, on the ground or into any body of water.
- Contact local authorities for further guidance.

Shipping Information

- Ship Domestic Ground
- Flammable Liquid, N.O.S. (Contains Pentane, Cyclohexane), Class 3, UN1993, PGI1

Physical Properties

Color:	Clear
Odor:	Slight Aromatic
Density:	5.85 lbs/gallon
Solids Content:	0%
VOC/liter of materials:	702 g/L (Calculated)
VHAP Content:	10 g/L (0.09 lbs/gal)
VOC*:	702 g/L (Calculated) *Less water & exempt solvents
Flashpoint:	-16.7° C/2° F (Closed Cup)
Composite part. pres.:	150 mm Hg @ 20° C
Nonphotochemically Reactive	

Primary Contents

Light hydrotreated distillate (CAS# 68410-97-9), n-Hexane (CAS# 110-54-3), n-Pentane (CAS#109-660-) and Cyclohexane (CAS# 110-82-7)

First Aid

Inhalation: At the first sign of overexposure (headache, nausea, dizziness), seek fresh air immediately. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Call physician immediately. *Eye Contact:* Immediately flush eyes with running water for at least 15 minutes. Get medical attention. *Skin Contact:* Immediately wash contacted areas of skin with soap and water. Remove contaminated clothing immediately; launder prior to reuse. *Swallowing:* If swallowed, call physician immediately. Do NOT induce vomiting unless directed to do so by a physician. NEVER give anything by mouth to an unconscious person. *Post the phone number of a doctor or poison control center at the nearest telephone.*



Extremely Flammable

ADHESIVE CLEANER
FOR REMOVING RESIDUE & OVERSPRAY



ADHESIVE CLEANER FOR REMOVING RESIDUE & OVERSPRAY

Safety

- **DANGER! EXTREMELY FLAMMABLE LIQUID AND VAPOR. VAPOR MAY CAUSE FLASH FIRE. HARMFUL OR FATAL IF SWALLOWED. VAPOR HARMFUL! MAY CAUSE EYE, SKIN AND RESPIRATORY TRACT IRRITATION. KEEP OUT OF REACH OF CHILDREN.**
- Use only in well ventilated area. Vapors may ignite explosively. Do not use or store near heat, spark or flame.
- Prevent buildup of vapors. Open all windows and doors. Do not smoke. Extinguish all flames and pilot lights. Turn off stoves, heaters, electric motors and other sources of ignition during use and until all vapors are gone.
- To eliminate static electricity when pouring the contents of this container into another one, attach a wire to both containers and connect the wire to ground.
- Use extreme caution when opening container in warm or hot environments as heat causes the solvent vapor to expand, generating high pressures.
- Never pressurize container.
- Avoid repeated breathing of vapors and mists. Avoid contact with eyes and skin. Do not take internally. Keep container closed when not in use.
- **Extremely flammable; Class 1B Flammable Liquid**
Do not cut, puncture, drill, grind or weld on or near this container. In case of fire use dry chemical, water fog, CO₂ or "alcohol foam". Water alone may be ineffective. See MSDS for complete data.
- **HMIS Rating: Health 2, Flammability 3, Reactivity 0;**
24 hr. Chemtrec emergency number:
1-800-424-9300 (US); 703-527-3887 (International)

Health Hazard Data/Target Organ Effects

- Contains materials that may cause lung, liver, kidney and central and peripheral nerve system damage.
- Inhalation of vapors may cause central nervous system depression (anesthetic effect) with headache, nausea and dizziness.
- Contained breathing of excessive amounts may be fatal.
- Prolonged or repeated skin contact may result in dermatitis.
- Ingestion may cause vomiting, dizziness and gastrointestinal irritation.

Warranty

Wilsonart International, Inc. warrants to the user that this product is free of defects for a period of two (2) years from the date of manufacture when it is applied in accordance with manufacturer's instructions or the manufacturer will replace the container at no cost or additional charge to the user, provided the unused portion of the product is returned to the place of purchase within 15 days of the date of purchase. This warranty does not apply to (I) products that are purchased after the expiration of the manufacturer's recommended shelf life as stated on this technical data sheet, (II) misuse or mishandling of the product, (III) improper storage, or (IV) improper fabrication using this product. NO OTHER WARRANTIES, EXPRESS OR IMPLIED ARE MADE, INCLUDING MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. UNDER NO CIRCUMSTANCES SHALL THE MANUFACTURER BE LIABLE FOR ANY LOSS OR DAMAGE ARISING FROM THE PURCHASE, USE, OR INABILITY TO USE THIS PRODUCT, OR FOR ANY SPECIAL, INDIRECT, INCIDENTAL OR CONSEQUENTIAL DAMAGES. NO FABRICATOR, INSTALLER, DEALER, AGENT OR EMPLOYEE OF WILSONART INTERNATIONAL, INC. HAS THE AUTHORITY TO MODIFY THE OBLIGATIONS OR LIMITATION OF THIS WARRANTY. This warranty gives you specific legal rights, and you may also have other rights which vary from state to state. Therefore, some of the limitations stated above may not apply to you. It is to your benefit to save your documentation upon purchase of product.

For More Information

- www.wilsonartadhesives.com for:
 - Tech Data Sheets
 - Material Safety Data Sheets (MSDS)
 - Adhesive Quick Reference Chart
 - Certified Product Data Sheets (CPDS)
- Customer Service Line 1-800-433-3222; adhesives@wilsonart.com
- Wilsonart International, Inc. - Adhesives Division
10601 NW HK Dodgen Loop
Temple, TX 76504