

121

ADHESIVE CLEANER

FOR REMOVING RESIDUE & OVERSPRAY



General Description

- A blend of acetone, toluene and light hydrotreated distillate that is designed to dissolve and remove dried adhesive overspray and residue from fabricated parts and decorative surfaces
- No smearing or leftover adhesive film after drying
- Effective by only dissolving the adhesive resins and not the rubber
- Professional use only
- Does NOT require stirring before use

Applications to Avoid

- Do not use this product to clean equipment (spray guns, fluid lines, hoses, spray pots, rollers, brushes, etc.).
- Do not use this product or any other to thin Wilsonart Adhesives.

Availability

1-gallon cans, 5-gallon pails, 55-gallon drums

General Use Instructions

Use only after you have read and understand the warnings, safety measures and first aid instructions printed on container. Apply and allow to dry only in a well ventilated area. Use outdoors when possible. If indoors, open all windows and doors, and shut off all sources of ignition.

For Adhesive Residue Removal

Dab rag in cleaner and lightly rub residue, increasing rubbing pressure as needed. Keep rag wet with cleaner for best results.

Storage/Shelf Life

- Close container tightly when not in use.
- Rotate stock.
- Shelf life expires 2 years from manufacture date.
- Store in a cool, well ventilated area and away from ignition sources.

Clean-up/Disposal

Dispose of waste cleaner and cleaner soaked rags in accordance with regulations. Empty container may contain hazardous residue or flammable vapors which may explode upon ignition. Do not allow in any sewers, on the ground or into any body of water. Contact local authorities for further guidance.

Primary Contents

Light hydrotreated distillate (CAS 68410979), n-Hexane (CAS 110543), n-Pentane (CAS 109660) and Cyclohexane (CAS 110827)

Shipping Information

- Ship Domestic Ground
- Flammable Liquids, N.O.S. (Contains pentane, cyclohexane), Class 3, UN1993, PGII

Precautionary Information

Refer to product label and material safety data sheet for Health & Safety information before using this product.

Warranty

Manufacturer and distributor of this product makes no warranties, express or implied. No warranty of merchantability or fitness for a particular purpose shall apply. The person using this product (the "user") is solely responsible for determining whether this product is appropriate and/or suitable for user's purpose and method of application. Limitation and exclusion of remedies and damages:

Physical Properties

| | |
|------------------------------------|--------------------------|
| Color: | Clear |
| Odor: | Slight Aromatic |
| Density: | 5.85 lbs/gallon |
| Solids Content: | 0% |
| VOC/liter of material: | 702 g/L (Calculated) |
| VOC(less water & exempt solvents): | 702 g/L (Calculated) |
| VHAP Content: | 10 g/L (0.09 lbs/gal) |
| Flashpoint: | -16.7°C/2°F (Closed Cup) |
| Composite part. pres.: | 245 mm Hg @ 20°C |
| Nonphotochemically Reactive | |

the exclusive and sole remedy, and the manufacturer and distributor's exclusive and sole obligation, for any defect of this product is the refund of the purchase price of the product. The manufacturer and distributor shall not, under any circumstances or under any legal theory, be liable to the purchaser or any other person for special, incidental or consequential damages of any nature, including without limitation damages to, or loss of use of, property, damages for loss of profits or revenues or any other damages arising from the purchase or use of the product. The manufacturer and distributor's liability will in no event exceed the purchase price of the product.

Contact

Customer Service: 1-800-433-3222 or adhesives@wilsonart.com
Visit www.wilsonartadhesives.com for information