

130

LOW VOC ADHESIVE SOLVENT FOR SPRAY SYSTEMS & EQUIPMENT

General Description

- A blend of acetone, toluene and Tert-Butyl acetate that is designed to remove adhesive residue from fabricated parts
- For detaching incorrectly bonded surfaces
- For clean-up of spray systems, tools and equipment
- Professional use only
- Does NOT require stirring before use

Applications to Avoid

Do not use this product or any other to thin Wilsonart Adhesives

Availability

5-gallon pails, 55-gallon drums

General Use Instructions

Use only after you have read and understand the warnings, safety measures and first aid instructions printed on container. Apply and allow to dry only in a well ventilated area. Use outdoors when possible. If indoors, open all windows and doors, and shut off all sources of ignition.

For Equipment Cleaning

For best results, clean equipment immediately after use. Brushes and rollers may be left to soak in Wilsonart 130.

For Adhesive Residue Removal

Dab rag in solvent and lightly rub residue, increasing rubbing pressure as needed. Do not flood surfaces during cleaning as solvent will attack bonds and cause edges and seams to lift.

For Detaching Incorrectly Bonded Surfaces

Apply Wilsonart 130 to the bondline. Keep the bondline constantly wet with Wilsonart 130. Pull surfaces gently apart as Wilsonart 130 loosens bond.

Storage/Shelf Life

- Close container tightly when not in use.
- Rotate stock.
- Shelf life expires 2 years from manufacture date.
- Store in a cool, well ventilated area and away from ignition sources.

Clean-up/Disposal

Dispose of waste solvent and solvent soaked rags in accordance with regulations. Empty container may contain hazardous residue or flammable vapors which may explode upon ignition. Do not allow in any sewers, on the ground or into any body of water. Contact local authorities for further guidance.

Primary Contents

Tert-Butyl Acetate (CAS 540885), Tert-Butyl Alcohol (CAS 75650), Acetone (CAS 67641) and Toluene (CAS 108883)

Shipping Information

- Ship Domestic Ground
- Flammable Liquids, N.O.S. (Contains butyl acetates, acetone & toluene), Class 3, UN1993, PGII

Precautionary Information

Refer to product label and material safety data sheet for Health & Safety information before using this product.

Physical Properties

Color:	Clear
Odor:	Strong Solvent
Density:	7.02 lbs/gallon
Solids Content:	0%
VOC/liter of material ¹ :	68 g/L (Calculated)
VHAP Content:	65 g/L (0.58 lbs/gal)
Flashpoint:	-12.2°C/10°F (Closed Cup)
Composite part. pres.:	<2 mm Hg @ 20°C
Nonphotochemically Reactive	

¹ TBAC IS RECOGNIZED IN 40 C.F.R. 51.100(s) AND BY THE EPA AS A VOC EXEMPT COMPOUND. ALASKA, CALIFORNIA, KANSAS, WYOMING AND WASHINGTON D.C. HAVE NOT FORMALLY RECOGNIZED THIS EXEMPTION. CONTACT YOUR LOCAL REGULATORY AGENCY TO PROVIDE CLARIFICATION ON THE EXEMPTION STATUS.

Warranty

Manufacturer and distributor of this product makes no warranties, express or implied. No warranty of merchantability or fitness for a particular purpose shall apply. The person using this product (the "user") is solely responsible for determining whether this product is appropriate and/or suitable for user's purpose and method of application. Limitation and exclusion of remedies and damages: the exclusive and sole remedy, and the manufacturer and distributor's exclusive and sole obligation, for any defect of this product is the refund of the purchase price of the product. The manufacturer and distributor shall not, under any circumstances or under any legal theory, be liable to the purchaser or any other person for special, incidental or consequential damages of any nature, including without limitation damages to, or loss of use of, property, damages for loss of profits or revenues or any other damages arising from the purchase or use of the product. The manufacturer and distributor's liability will in no event exceed the purchase price of the product.

Contact

Customer Service: 1-800-433-3222 or adhesives@wilsonart.com
Visit www.wilsonartadhesives.com for information