



700
701

General Description

A blend of synthetic rubbers in non-chlorinated organic solvents that delivers rapid, high-strength bonds. This product does not require stirring before use.

Applications

- FOR PROFESSIONAL USE ONLY
- Non-chlorinated
- Self-contained spray applications

Applications to Avoid

- Application to copper or copper alloys, and use of copper-containing application systems or components
- Surfaces with dirt, grease or excessive moisture
- Vinyl surfaces containing plasticizers which may attack the bond (conduct pre-testing if in doubt)
- Postforming requirements

Availability

- 300 lbs canister (returnable), red or natural
- 140 lbs canister (returnable), red or natural
- 30 lbs canister (non-returnable), red or natural
- 9 lbs canister (non-returnable), red or natural

Storage/Shelf Life

- Keep container valve OPEN when not in use. Keep spray gun thumbwheel CLOSED when not in use.
- Rotate stock.
- Shelf life expires 1 year from manufacture date.
- Store in a well ventilated area and away from ignition sources.
- Canister may not spray when cold and must be warmed to room temperature.

Equipment Specifications

- Standard spray gun: AA23L-45885-SS
- Hoses available: 6', 12', 18' and 24'
- Available gun tips: 6501 (65° fan), 4001 (40° fan)

General Use Instructions

DO NOT USE THIS PRODUCT IF YOU HAVE NOT READ OR DO NOT UNDERSTAND THE WARNINGS, SAFETY MEASURES AND FIRST AID INSTRUCTIONS PRINTED ON THE CONTAINER OR LABEL.

- Before assembly, rotate gun thumbwheel closed so that trigger can not be pulled. Securely attach gun to hose, then hose to canister. Fully open canister valve. DO NOT CLOSE UNTIL CANISTER IS EMPTY.
- Assemble all parts at or above 65°F. Allow all substrates to acclimate to room temperature for 48 hours before bonding. Ensure all surfaces are clean and dry.

Physical Properties

Color:	Red (700); Natural (701)
Density:	5.9 lbs/gallon
VOC (Less water & exempt solvents):	490 g/L (Calculated)
VHAP Content:	0.21 lbs/lbs solids
Flashpoint:	-94° C/-138° F (from formula)
Coverage:	20-25 bonded ft ² /lb at 2.5 dry grams/ft ²
Open Time:	~30 minutes

***Qualifies for LEED[®]-NC & CI EQ Credit 4.4:**

Laminating adhesives shall contain no added urea-formaldehyde resins.

- Spray with gun tip 6 - 10 inches from surface. Keep gun perpendicular (90°) to surface. Apply the adhesive uniformly. Cover 80% - 100% of each surface and 100% of edges with a minimum coverage rate of 2.5 dry grams/ft².
- Allow approximately 3 - 5 minutes to dry after application and before bonding. When ready to bond, each surface will be tacky but adhesive should not transfer or "leg" to a firmly pressed fingertip. If parts do not stick immediately, they have exceeded the open time. Over-dry parts can be reactivated by applying a light coat of fresh adhesive on both parts.
- Apply uniform downward pressure (30 - 40 psi minimum) over entire bonded surface. Mechanical pressure (pinch rolling) is recommended, but a 3" wide rubber J-roller is acceptable. Use of a wooden block or other hand rollers is not recommended.
- Immediate trimming and finishing is possible.



**Extremely Flammable
Spray Grade Canisterized**

**CONTACT ADHESIVE
FOR FLATWORK APPLICATIONS**



CONTACT ADHESIVE FOR FLATWORK APPLICATIONS

Clean-up/Disposal

- Clean gun tip by dabbing with masking tape.
- Clean equipment with WA 110 solvent.
- When application completed, leave gun and hose attached to canister, but rotate gun thumbwheel closed to prevent accidental gun discharge or adhesive drying in hose.
- When changing canisters, quickly disconnect and reconnect the gun/hose assembly to prevent adhesive from drying and clogging system.
- Do not allow in any sewers, on the ground or into any body of water.
- Contact local authorities for further guidance.

Extremely flammable liquefied gas under pressure.

Do not cut, puncture, drill, grind or weld on or near this container.

Shipping Information

- SHIP DOMESTIC GROUND ONLY; DO NOT SHIP BY AIR
- Liquefied gas, flammable, n.o.s (dimethyl ether, hexane), 2.1, UN 3161

Primary Contents

- Acetone (CAS 67-64-1)
- Toluene (CAS 108-88-3)
- Propane (CAS 74986)
- Isobutane (CAS 75285)
- Dimethyl ether (CAS 115106)
- n-Hexane (CAS 110543)

California Proposition 65 Warning

This product contains substances known to the State of California to cause cancer or reproductive harm.

Volatile Organic Compounds (VOC):

The use, supply, sale or offer for sale of this product in certain states and localities may be prohibited if it exceeds certain VOC limits. Please check state and local regulations for any prohibitions on the sale and use of this product.

First Aid

Inhalation: At the first sign of overexposure (headache, nausea, dizziness), seek fresh air immediately. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Call physician immediately. **Eye Contact:** Immediately flush eyes with running water for at least 15 minutes. Get medical attention. **Skin Contact:** Immediately wash contacted areas of skin with soap and water. Remove contaminated clothing immediately; launder prior to reuse. **Swallowing:** If swallowed, call physician immediately. Do NOT induce vomiting unless directed to do so by a physician. NEVER give anything by mouth to an unconscious person. *Post the phone number of a doctor or poison control center at the nearest phone.*

Safety

- DANGER! EXTREMELY FLAMMABLE LIQUID AND VAPOR. VAPOR MAY CAUSE FLASH FIRE. VAPOR MAY TRAVEL TO AREAS AWAY FROM WORK SITE BEFORE IGNITING/FLASHING BACK TO VAPOR SOURCE. KEEP AWAY FROM SPARKS, FLAME, OPEN LIGHT OR ANY SOURCE OF IGNITION. KEEP AWAY FROM OXIDIZERS. HARMFUL OR FATAL IF SWALLOWED. VAPOR HARMFUL! MAY CAUSE EYE, SKIN AND RESPIRATORY TRACT IRRITATION.
- KEEP OUT OF REACH OF CHILDREN!
- Apply and dry only with approved ventilation and adequate exhaust. Consult local authorities.
- Prevent buildup of vapors. Open all windows and doors. Do not smoke. Extinguish all flames and pilot lights. Turn off stoves, heaters electric motors and other sources of ignition during use and until all vapors are gone.
- Avoid repeated breathing of vapors. Avoid contact with skin. Do not take internally. Keep container closed when not in use.

- In case of fire, use dry chemical, water fog, CO₂ or "alcohol foam". Water alone may be ineffective. Irritating to eyes, skin and respiratory tract.
- See MSDS for complete data
- **HMIS Rating: Health 2, Flammability 4, Reactivity 1;**
24 hr. Chemtrec Emergency number:
1-800-424-9300 (US); 703-527-3887 (International)

Warranty

Wilsonart International, Inc. warrants to the user that this product is free of defects for a period of one (1) year from the date of manufacture when it is applied in accordance with manufacturer's instructions or the manufacturer will replace the container at no cost or additional charge to the user, provided the unused portion of the product is returned to the place of purchase within 15 days of the date of purchase. This warranty does not apply to (I) products that are purchased after the expiration of the manufacturer's recommended shelf life as stated on this technical data sheet, (II) misuse or mishandling of the product, (III) improper storage, or (IV) improper fabrication using this product. NO OTHER WARRANTIES, EXPRESS OR IMPLIED ARE MADE, INCLUDING MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. UNDER NO CIRCUMSTANCES SHALL THE MANUFACTURER BE LIABLE FOR ANY LOSS OR DAMAGE ARISING FROM THE PURCHASE, USE, OR INABILITY TO USE THIS PRODUCT, OR FOR ANY SPECIAL, INDIRECT, INCIDENTAL OR CONSEQUENTIAL DAMAGES. NO FABRICATOR, INSTALLER, DEALER, AGENT OR EMPLOYEE OF WILSONART INTERNATIONAL, INC. HAS THE AUTHORITY TO MODIFY THE OBLIGATIONS OR LIMITATION OF THIS WARRANTY. This warranty gives you specific legal rights, and you may also have other rights which vary from state to state, therefore, some of the limitations stated above may not apply to you. It is to your benefit to save your documentation upon purchase of product.

For More Information

- www.wilsonartadhesives.com for:
 - Tech Data Sheets
 - Material Safety Data Sheets (MSDS)
 - Adhesive Quick Reference Chart
 - Certified Product Data Sheets (CPDS)
- Customer Service Line 1-800-433-3222
- Wilsonart International, Inc. - Adhesives Division
10601 NW HK Dodgen Loop
Temple, TX 76504